



LEAD FINISH: GOLD	
CASING FINISH: GOLD	
CAPACITANCE	100pF
TEMP. RANGE	-55°C TO 125°C
CURRENT	5 AMP MAX.
WORKING VOLTAGE	125°C 115 VAC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHz	I.L. (db)
10	--
30	--
100	3
300	10
1 GHz	20
10 GHz	28
SCHEMATIC	



- NOTES:
1. SUGGESTED MOUNTING HOLE =  $\phi.132 \pm .002$
  2. MAX SOLDERING TEMP: 260°C FOR 20 SECONDS MAX

MARKING:

PART: GREEN DOT

BAG:  
SCI 9920-101  
DATE CODE  
QTY./BAG (100 MAX.)

	13					REV. NO.	TOLERANCES UNLESS OTHERWISE SPECIFIED	FAIRVIEW PENNSYLVANIA SPECTRUM CONTROL INC.	
	CN53938-ENG	12	11	10	09	08	Fractions ± 1/64		
		CN 209789					Dec. .xx ± .03	Dwn. KAUFFMAN	Description
		CN 202460					Dec. .xxx ± .005	Ckd. 4-20-10	FEEDTHRU FILTER
		CN 200034					Angles ± 0° 30'	Apvd.	
		CN 190154					CODE IDENT. NO. DLSP2	Scale NONE	SCI-9920-101
		CN 185016					CHANGE NOTICE		